

PT204 - GREEN POLYESTER TAPE 204 °C



- The thickness of our Polyester Tape is 60 microns and has a pressure sensitive silicone backing adhesive specially designed to prevent the formation of residues
- Its flexibility makes it conformable and particularly suitable for non leak seals.
- Applicable manually or with a machine thanks to its consistent unwinding force.
- Specially suited for all kind of masking (wet coating, E-coating, Anodizing, Photo splicing). It actually protects them from chemicals and splashes.

SPECIFICATIONS		
Reference	PT204	
Colour	Green	
Tape Thickness		
Film	0.038 mm	
Total	0.070mm	
Backing type	Polyester	
Adhesive type	Silicone	
Adhesion to Steel (N/25MM)	7-8	
Tensile Strength (N/25MM)	≥120	
Elongation at Break (%)	≥170	
Breakdown strength (N/25MM)	≥150	
Storage Condition	20°C / 65%R.H	68 °F / 65%R.H
Voltage resistance (KV)	4	
Maximum Temperature Resistance	204°C	399.2 °F
Length per roll	66m	72 yd
Width	5~500mm	0.2~19.68 inch

- Our tapes always have a plastic core and are shrink wrapped

GLOBALMASK is fully committed to the manufacture and supply of a wide family of masking products. We supply them since many years, and our customers are fully satisfied with the quality of our products. We are proud to listen to our customers demands with the objective to continuously increase our product portfolio without compromising their performance.

Our quality control procedures are applied during the production of all our masking products.

GLOBALMASK reserves the right to modify products with, however, the intention to improve their performance. In such a case we will always keep our customers informed.