



- The thickness of our Glass Cloth tape is 180 microns and has a pressure sensitive silicone backing adhesive specially designed to prevent the formation of residues after peeling off
- Our Glass Cloth Tape has the Insulation Grade H
- Its flexibility makes it conformable and particularly suitable for non leak seals.
- Specially suited for powder coating, electrical Insulation, wire wrapping, thermal insulation gaskets, sand blasting, shot blasting, grit blasting, plasma spray, thermal spray.

SPECIFICATIONS

Reference	GLT	
Colour	WHITE	
Tape Thickness		
Film	0.13mm	5.12 mil
Adhesive	0.05 mm	1.97 mil
Total	0.18 mm	7.09 mil
Backing type	Glass Cloth	
Adhesive type	Silicone	
Adhesion to Steel (N/10mm)	5.0-6.0	
Tensile Strength (N/10mm)	250	
Elongation at Break (%)	10	
Storage Condition	20°C / 65%R.H	68 °F / 65%R.H
RoHS	approved	
Maximum Temperature Resistance	280°C	482 °F
Length per roll	33m	36,09 yd
Width	5~500 mm	0.2~19.68 inch

- Our tapes always have a plastic core and are shrink wrapped

GLOBALMASK is fully committed to the manufacture and supply of a wide family of masking products. We supply them since many years, and our customers are fully satisfied with the quality of our products. We are proud to listen to our customers demands with the objective to continuously increase our product portfolio without compromising their performance. Our quality control procedures are applied during the production of all our masking products. GLOBALMASK reserves the right to modify products with, however, the intention to improve their performance. In such a case we will always keep our customers informed.