



- The thickness of our Polyester Tape is 60 microns and has a pressure sensitive silicone backing adhesive specially designed to prevent the formation of residues
- Its flexibility makes it conformable and particularly suitable for non leak seals.
- Applicable manually or with a machine thanks to its consistent unwinding force.
- Specially suited for all kind of masking (wet coating, E-coating, Anodizing, Photo splicing). It actually protects them from chemicals and splashes.

SPECIFICATIONS

| | | |
|--------------------------------|---------------|----------------|
| Reference | PT204 | |
| Colour | Green | |
| Tape Thickness | | |
| Film | 0.038 mm | |
| Total | 0.060mm | |
| Backing type | Polyester | |
| Adhesive type | Silicone | |
| Adhesion to Steel (N/25MM) | 7-8 | |
| Tensile Strength (N/25MM) | ≥120 | |
| Elongation at Break (%) | ≥170 | |
| Breakdown strength (N/25MM) | ≥150 | |
| Storage Condition | 20°C / 65%R.H | 68 °F / 65%R.H |
| Voltage resistance (KV) | 4 | |
| Maximum Temperature Resistance | 204°C | 399.2 °F |
| Length per roll | 66m | 72 yd |
| Width | 5~500mm | 0.2~19.68 inch |

•Our tapes always have a plastic core and are shrink wrapped

GLOBALMASK is fully committed to the manufacture and supply of a wide family of masking products. We supply them since many years, and our customers are fully satisfied with the quality of our products. We are proud to listen to our customers demands with the objective to continuously increase our product portfolio without compromising their performance. Our quality control procedures are applied during the production of all our masking products. GLOBALMASK reserves the right to modify products with, however, the intention to improve their performance. In such a case we will always keep our customers informed.