



- The thickness of our Polyester Tape 1510 is 150 microns and has a pressure sensitive silicone backing adhesive specially designed to prevent the formation of residues.
- Specially created for high tack and abrasive applications.
- Our strong Polyester film substrate helps to avoid its damage once removed.
- Its flexibility makes it conformable and particularly suitable for non leak seals.
- Applicable manually or with a machine thanks to its consistent unwinding force.
- Specially suited for all kind of masking (Powder coating, E-coating, Anodizing, Photo splicing) including circuit boards. It actually protects them from chemicals and splashes.

SPECIFICATIONS		
Reference	GPT	
Colour	Green	
Tape Thickness		
Film	0.100 mm	3.94 mil
Adhesive	0.050 mm	1.97 mil
Total	0.150 mm	5.91 mil
Backing type	Polyester	
Adhesive type	Silicone	
Adhesion to Steel (ASTM D1000)	280~480 N/m	
Tensile Strength (ASTM D882)	>10.000 N/m	
Elongation at Break (ASTM D882)	30%	
Storage Condition	20°C / 65%R.H	68 °F / 65%R.H
Dielectric strength	4.0 KV	
Maximum Temperature Resistance	204°C	400 °F
Length per roll	66m	72 yd
Width	5~500 mm	0.2~16.68inch

•Our tapes always have a plastic core and are shrink wrapped

GLOBALMASK is fully committed to the manufacture and supply of a wide family of masking products. We supply them since many years, and our customers are fully satisfied with the quality of our products. We are proud to listen to our customers demands with the objective to continuously increase our product portfolio without compromising their performance.

Our quality control procedures are applied during the production of all our masking products.

GLOBALMASK reserves the right to modify products with, however, the intention to improve their performance. In such a case we will always keep our customers informed.