

SILICONE LEADING PULL PLUG

REFERENCE:

LT200-

DESCRIPTION:

Silicone Leader Pull Plug

MATERIAL:

High temperature Silicone 315°C

See the material data sheet

DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Leader Pull Plug is according the RMA A3

APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

Used to mask both chamfers of a through hole. Range of sizes from M4 to M16

RECOMMENDATIONS for USE:

Choose the plug that adapts to the Metric dimension of the Hole to mask. Fix the plug in the hole passing the handle trough the hole and pulling it until the first flange are on the first screw line while the last flange fits perfectly on the last screw line

In The right masking position this plug must cover the first and the last screw of the hole.

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process.

Chemical products may reduce the useful life of the product.

