

## SC

### REFERENCE:

SC

### DESCRIPTION :

Silicone Cap 315°C

### MATERIAL:

*High temperature Silicone 315°C*

See the material data sheet

### DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Cap is according the RMA A3

### APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

### USES:

This cap is used to mask studs and bolts.

### RECOMMENDATIONS for USE:

The inner diameter "A" should be between 0.3 and 0.5 mm below the diameter of the bolt to be protected so the cover fits well and doesn't fall during the process.

Choose the most appropriate cover length "C" for the length to be hidden.

### STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

### EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

### USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process. Chemical products may reduce the useful life of the product.

