

Silicone Easy Cap

REFERENCE:

SCE

DESCRIPTION:

Silicone Easy Cap 315°C

MATERIAL:

High temperature Silicone 315°C

See the material data sheet



DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Easy Cap is according the RMA A3

APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

The Easy cap is used to mask studs with two similar different diameters and also to mask long studs where the fitting becomes difficult because of the high level of friction it appears between the cap and the stud to be masked.

RECOMMENDATIONS for USE:

The smaller inner diameter "A" should be between 0.3 and 0.5 mm below the diameter of the stud.

Choose the appropriate length "L" of the Easy Cap.

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process.

Chemical products may reduce the useful life of the product.