

SILICONE THREAD MASK PLUG

REFERENCE:

TMP

DESCRIPTION:

Silicone Thread Mask Plug 315°C

MATERIAL:

High temperature Silicone 315°C

See the material data sheet

DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Thread Mask Plug is according the RMA A3

APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

Used to mask a hole and the first thread line. Range of sizes from M5 to M22. The Plug is fixed by pushing.

RECOMMENDATIONS for USE:

Choose the plug that adapts to the Metric dimension of the Hole to be masked. Fix the plug by pushing it into the hole until the first flange is on the first screw line.

If the hole is not a Metric system Dimension, then chose the TMP reference with an "A" dimension as similar as possible to the hole diameter and always a little bigger (0.2 or 0.3 mm bigger)

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process.

Chemical products may reduce the useful life of the product.

