

Flangeless PLUG

REFERENCE:

UFP

DESCRIPTION:

Silicone Flangeless Plug 315°C

MATERIAL:

High temperature Silicone 315°C

See the material data sheet

DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Flangeless Plug is according the RMA A3

APLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

Used to cover M5 to M28 threaded holes.

This plug is used to mask a hole and the first screw thread because of the corrugated design.

Given the conical shape, the same reference can plug slightly different hole dimensions by adjusting it to the appropriate size required for each use. The pull is sturdy so it doesn't break while installing or removing the plug.

RECOMMENDATIONS for USE:

The size of the hole to be hidden must be between the largest and smallest diameter of the plug "A" and "B".

This plug is inserted with a bit of pressure. The plug should not be threaded when installing it in the hole as the screw threads will cut the plug. Once installed, the plug must be secure. It is recommended that no more than half of the plug sticks out so it doesn't fall during the process.

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process. Chemical products may reduce the useful life of the product.

