

SILICONE HOLLOW CONE PLUG

REFERENCE:

UHCP

DESCRIPTION:

Silicone Hollow Cone Plug

MATERIAL:

High temperature Silicone 315°C

See the material data sheet

DIMENSIONAL TOLERANCE

The dimensional tolerance of the Silicone Hollow Cone Plug is according the RMA A3

APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

This Hollow plug is used to mask holes. Since it is Conical It can adjust easily in many different diameters and as it is hollow inside it fits easily and tight to the hole.

RECOMMENDATIONS of USE:

The Silicone Hollow Conical Plug just has two different sizes.

The diameter of the hole to be masked must be between the bigger and the smaller diameter "A" and "B". It can be fixed by pushing or by pulling it through the hole to mask.

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process. Chemical products may reduce the useful life of the product.

