

HANDLE CONICAL PLUG

REFERENCE:

UP

DESCRIPTION:

Handle Conical Plug 315°C

MATERIAL:

High temperature Silicone 315°C

See the material data sheet

DIMENSIONAL TOLERANCE

The dimensional tolerance of the Handle Conical Plug is according the RMA A3

APPLICATIONS:

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

USES:

Used to cover M3 to M24 threaded or flat holes.

The pull means the plug can be installed flush with the surface to prevent protruding paint excess and so it can be removed quickly and easily. Given the Conical shape, the same reference can be used to mask different hole diameters by adjusting it to the appropriate size required for each use.

RECOMMENDATIONS for USE:

The size of the hole to be hidden must be between the largest and smallest diameter of the plug ("B" and "A")

If the plug sticks out too much it may fall during use meaning it is best to choose a plug that is as flush as possible.

STORAGE RECOMMENDATIONS:

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

EXPIRY

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

USEFUL LIFE OF THE PRODUCT

The useful life of this product depends on the conditions and loads it is subjected to during the process. Chemical products may reduce the useful life of the product.

