

## **SILICONE CONE CAP**

### **REFERENCE:**

HWP-

### **DESCRIPTION:**

Silicone Cone Cap 315°C

### **MATERIAL:**

*High temperature Silicone 315°C*

See the material data sheet

### **DIMENSIONAL TOLERANCE**

The dimensional tolerance of the Silicone Cone Cap is according the RMA A3

### **APPLICATIONS:**

Powder Coating, Wet Coating, E-Coating, Plating, Anodizing.

### **USES:**

This Cone Cap is used to mask Holes and the closest surrounding area. The Hollow inside part makes it very flexible and easy to fix on the hole.

### **RECOMMENDATIONS for USE:**

The outer diameter "B" should be between 0.5 and 1.5 mm below the diameter of hole to be protected so the plug fits well and doesn't fall during the process.

Choose the most appropriate washer diameter "A" to mask the surrounding area.

### **STORAGE RECOMMENDATIONS:**

Storing this product away from direct sunlight and at a temperature between 20° C and 25° C is recommended in order to prevent any modifications to the properties such as flexibility, elasticity or decolouring, among others.

The material this product is made of possesses no health risk nor is it considered hazardous requiring consideration when handling or storing it.

### **EXPIRY**

This product does not expire, but it may lose plasticity and flexibility if stored inappropriately and/or for more than 5 years.

### **USEFUL LIFE OF THE PRODUCT**

The useful life of this product depends on the conditions and loads it is subjected to during the process.

Chemical products may reduce the useful life of the product.

